

T2265 Serial Printer

Enough Speed To Tackle Any Industry Applications!

At top speeds of 900 cps the T2265 keep pace with the bustling, demanding world where printing is time sensitive and critical. Engineered for printing under adverse conditions, these devices produce multi-part invoices, shipping documents or bar code labels at a rate of 40,000 pages per month.



Affordable Upgrades.

Optionally configured with three input tractors (two front, one rear). The T2265 is expandable to two front input tractors. A straight paper path on the front tractors of the T2265 result in jam-free operation and flawless 24-wire impressions on up to 6-part forms. The T2265 offers fully automated gap adjustment, paper parking, and loading.

Ideal For Many Markets & Applications.

Federal, State & Local Government- Print tax forms, payroll checks, expense reports, inventory reports, invoices.

Manufacturing, Transportation, & Distribution - Print pick lists, shipping labels and freight bills. Excellent readability on all industry standard bar codes, including POSTNET.

Healthcare (MEDITECH APPROVED) - The T2265G are MEDITECH approved and handle a wide variety of media including bar code labels for patient chart.

Product Highlights

High speed and rugged design for easy use and heavy duty operation.
Designed for service-free PC, network and mini system operations.
900 characters per second/540 pages per hour in draft mode.
Handles up to 6-part forms with no skewing or jamming.
automatically adjusts for different forms thickness.
Easy to access, straight paper path for reliable forms handling.

Available Configuration:

T2265 - Wide Carriage, Single Tractor, Centronics Parallel

Features & Specifications

Print Speed	At 10, 12, 15 cpi: Draft 650, 720, 900; NLQ 200, 240, 300; LQ 100, 120, 150
Print Method	Serial Impact
Resolution	360 x 360 dpi
Throughput	540 pages per hour (ECMA 132/6.91, draft)
Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi (Emulation dependent)
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	Printhead Life: 500 M Characters (draft)
Standard Connectivity	Bi-directional Centronics Parallel
Optional Connectivity	Ethernet, RS232 Serial
Standard Emulation	IBM® Proprinter XL24e, Epson® LQ-2550, Epson® LQ-2170 (ESC P/2), MTPL
Optional Emulation	LA75
Fonts	Draft, Copy Draft, Courier, Roman, Sans Serif, OCR A, OCR B, 15 Bar Codes & scaleable LCP fonts.
Consumables	20 M Character Ribbon
STD Paper Handling	Front insertion, Push tractor with paper parking and AGA
Opt'l Paper Handling	Front push tractor, automatic dual-bin sheet feeder (190 sheets per bin), face down output, paper cutter. Paper: Length: 4" min, 14" max; Width: 4" min, 14.5" max.
Number of Copies	Original + 5 (6-part forms)
Paper Cutting	optional cutter
Paper Type	Continuous paper, cut sheets (optional feeder)
Paper Size	Paper: Length: 4" min, 14" max; Width: 4" min, 14.5" max
Physical Weight	42 lbs
Physical Size	24.5" x 10.9" x 16.9"
Power Voltage	AC 230V and 120V (selectable)
Power Frequency	50/60Hz
Power Consumption	60 Watts
Compliance	Energy Star compliant, Ozone-free
Workload	Up to 40,000 pages per month
Reliability MTBF	10,000 hours @ 100% duty cycle
Drivers	Windows XP, Server 2003, 2000, 95/98/ME, NT 4.0, 3X; SAP
Temperature	+10°C to +35°C
Humidity	16% to 73% (relative humidity)
Acoustic	53 dB (ISO 7779)
Warranty	One year limited on site. First 90 days - parts, labor and travel
Option 1	Second front push tractor, Paper cutter, dual bin sheet feeder
Option 2	Ethernet, RS232 Serial
Option 3	printer stand, paper basket, pedestal cabinet, cable cover, castors
Note	Exceeding the monthly duty cycle will not void the warranty if TallyGenicom consumables and maintenance kits are used.



Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Published Date: 03/30/2006 Copyright © 2006 TallyGenicom, L.P.



4500 Daly Drive, Suite 100
Chantilly, VA 20151
T 800.436.4266
www.tallygenicom.com

