

## T2280 Serial Printer

For Where Printing Is Time Sensitive And Critical



At top speeds of 1,100 the T2280 keeps pace with the bustling, demanding world where printing is time sensitive and critical. Engineered for printing under adverse conditions, these devices produce multi-part invoices, shipping documents or bar code labels at a rate of 50,000 pages per month.

### **Affordable Upgrades.**

Optionally configured with three input tractors (two front, one rear), the T2280 is priced 50% lower than the competition. A straight paper path on the front tractors of the T2280 results in jam-free operation and flawless 24-wire impressions on up to 7-part forms. The T2280 offers fully automated gap adjustment, paper parking, loading, etc.

### **Ideal For Many Markets & Applications.**

Federal, State & Local Government- Print tax forms, payroll checks, expense reports, inventory reports, invoices.

Manufacturing, Transportation, & Distribution - Print pick lists, shipping labels and freight bills. Excellent readability on all industry standard bar codes, including POSTNET.

### **Product Highlights**

High speed and rugged design for easy use and heavy duty operation.  
Designed for service-free PC, network and mini system operations.  
1,100 characters per second/600 pages per hour in draft mode.  
Handles up to 7-part forms with no skewing or jamming.  
Automatically adjusts for different forms thickness.  
Easy to access, straight paper path for reliable forms handling.

---

Available Configuration:

**T2280** - Wide Carriage, Single Tractor, Parallel  
**T2280-2T** - Wide Carriage, Dual Tractor, Parallel

## Features &amp; Specifications

<b>Print Speed</b>	At 10, 12, 15 cpi: Draft 800, 880, 1100; NLQ 245, 295, 370; LQ 120, 145, 185
<b>Print Method</b>	Serial Impact
<b>Resolution</b>	360 x 360 dpi
<b>Throughput</b>	600 pages per hour (ECMA 132/6.91 draft)
<b>Character Density</b>	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi (Emulation dependent)
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Printhead Life</b>	Printhead Life: 500 M Characters (draft)
<b>Standard Connectivity</b>	Bi-directional Centronics Parallel
<b>Optional Connectivity</b>	Ethernet, RS-232 Serial
<b>Standard Emulation</b>	IBM® Proprinter XL24e, Epson® LQ-2550, Epson® LQ-2170 (ESC P/2), MTPL
<b>Optional Emulation</b>	LA75
<b>Fonts</b>	Draft, Copy Draft, Courier, Roman, Sans Serif, OCR A, OCR B, 15 Bar Codes & scaleable LCP fonts
<b>Consumables</b>	20 M Character Ribbon
<b>STD Paper Handling</b>	Front insertion, Push tractor with paper parking and AGA
<b>Opt'l Paper Handling</b>	Additional front push tractor, automatic dual-bin sheet feeder (190 sheets per bin), face down output, paper cutter. Paper: Length: 4" min, 14" max; Width: 4" min, 14.5" max.
<b>Number of Copies</b>	Front: Original + 6 (7-part forms); Back: Original + 4 (5-part forms)
<b>Paper Type</b>	Continuous paper
<b>Paper Weight</b>	NA
<b>Paper Size</b>	Length: 4" min, 14" max; Width: 4" min, 14.5" max
<b>Physical Weight</b>	42 lbs
<b>Physical Size</b>	24.5" x 10.9" x 16.9"
<b>Power Voltage</b>	AC 230V and 120V (selectable)
<b>Power Frequency</b>	50/60H
<b>Power Consumption</b>	70 Watts
<b>Compliance</b>	Energy Star compliant, Ozone-free
<b>Workload</b>	Up to 50,000 pages per month
<b>Reliability MTBF</b>	10,000 hours @ 100% duty cycle
<b>Drivers</b>	Windows XP, Server 2003, 2000, 95/98/ME, NT 4.0, SAP
<b>Temperature</b>	+10°C to +35°C
<b>Humidity</b>	16% to 73% (relative humidity)
<b>Acoustic</b>	53 dB (ISO 7779)
<b>Warranty</b>	One year limited on site. First 90 days - parts, labor and travel
<b>Option 1</b>	Second front push tractor, Paper cutter, dual bin sheet feeder
<b>Option 2</b>	Ethernet, RS232 Serial
<b>Option 3</b>	printer stand, paper basket, pedestal cabinet, cable cover, castors
<b>Note</b>	Exceeding the monthly duty cycle will not void the warranty if TallyGenicom consumables and maintenance kits are used



Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Published Date: 03/30/2006 Copyright © 2006 TallyGenicom, L.P.



4500 Daly Drive, Suite 100  
Chantilly, VA 20151  
T 800.436.4266  
www.tallygenicom.com

